International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
Peer Reviewed, Referred & Indexed Journal
ISSN: 3068-272X www.ijdim.com Original Research Paper

Intelligent Authentication Techniques for Secure Mobile Devices

Tharun[1], Dr.G.Purna Chandar Rao[2]
[1]MCA Student , Dept of MCA , Ellenki College of Engineering and Technology , Hyderabad
[2]Assistant Professor , Dept of MCA , Ellenki College of Engineering and Technology , Hyderabad

***Abstract*— Mobile devices have become an essential part of everyday life, allowing users to access banking, healthcare, social media, and other sensitive services. As the amount of personal information stored on smartphones continues to grow, protecting these devices from unauthorized access has become increasingly important. This project presents a secure authentication system that uses fingerprint-based biometric verification instead of traditional password authentication. The proposed system is developed using Python and Django and applies Harris Corner Detection along with ORB feature extraction to compare fingerprint images during user registration and login. The system verifies whether the uploaded fingerprint matches the one stored in the database before granting access. This approach enhances security by reducing the risks associated with stolen or weak passwords while providing a reliable and user-friendly authentication process. The proposed solution demonstrates that biometric authentication offers improved protection for mobile applications and can be extended to Android-based systems for secure user access.**

***Keywords* — Mobile Device Security, Biometric Authentication, Fingerprint Recognition, Harris Corner Detection, ORB Feature Extraction, User Authentication, Python, Django, Mobile Application Security.**

I. INTRODUCTION

The rapid growth of mobile technology has transformed smartphones into powerful computing devices that support communication, online banking, digital payments, healthcare services, education, and social networking. As users increasingly rely on mobile devices to store sensitive personal and financial information, ensuring secure access has become a major challenge. Traditional authentication methods such as passwords, PINs, and pattern locks provide an initial level of protection, but they are vulnerable to password guessing, shoulder surfing, phishing attacks, and unauthorized access when the device remains unlocked. These limitations have encouraged researchers to explore stronger and more reliable authentication mechanisms that improve both security and user convenience [5], [11].

Biometric authentication has emerged as one of the most effective solutions for mobile device security. Unlike knowledge-based authentication methods, biometric techniques verify users based on unique physiological or behavioral characteristics such as fingerprints, facial features, iris patterns, voice, and touch behavior. Since these characteristics are difficult to imitate or steal, biometric authentication offers a higher level of protection against unauthorized access. Fingerprint authentication, in particular, has become one of the most widely adopted methods due to its speed, accuracy, and ease of use in modern smartphones [6].

Recent research has also focused on continuous authentication, where the identity of the user is verified throughout the device usage session instead of only during login. Behavioral biometric traits such as touch gestures, scrolling patterns, typing dynamics, and device movement can continuously monitor user identity without interrupting normal device operation. These techniques improve security by detecting unauthorized users even after the device has been unlocked [3], [4], [8]. Studies have shown that scrolling interactions and touch behavior contain distinctive patterns that can accurately identify users while maintaining a seamless user experience [1], [5], [7].

This project presents a fingerprint-based authentication system for enhancing mobile device security using Python and Django. The proposed system employs Harris Corner Detection and ORB feature extraction to compare fingerprint images captured during user registration and login. The extracted feature points are matched to determine the authenticity of the user before granting access to the application. This approach provides a secure and efficient authentication mechanism while reducing the risks associated with traditional password-based systems. Furthermore, the proposed framework demonstrates how biometric authentication can be integrated into web-based and mobile applications to improve user privacy, data protection, and overall system security. The project aims to deliver a

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
Peer Reviewed, Referred & Indexed Journal
ISSN: 3068-272X www.ijdim.com Original Research Paper

reliable authentication solution that combines usability, accuracy, and enhanced protection against unauthorized access by leveraging established biometric recognition techniques and feature matching algorithms [9], [10], [12].

II. RELATED WORK

"Continuous User Identification via Touch and Movement Behavioral Biometrics," C. Bo, L. Zhang, T. Jung, J. Han, X.-Y. Li, and Y. Wang [3]

This paper proposed a continuous authentication framework called SilentSense that combines touch behavior and device movement patterns to identify smartphone users. The authors observed that every individual interacts with a touchscreen differently, producing unique touch dynamics and motion characteristics. By collecting sensor data such as accelerometer readings along with touch events, the system continuously verified user identity without interrupting normal device usage. Experimental evaluation demonstrated that integrating touch behavior with movement biometrics significantly improved authentication accuracy, achieving over 99% identification performance under different operating conditions. The framework effectively detected unauthorized users while remaining transparent to legitimate users. The study proved that combining multiple behavioral biometric traits enhances security compared to single-feature authentication methods. This research strongly supports the development of intelligent continuous authentication systems for modern mobile devices.

"Information Revealed from Scrolling Interactions on Mobile Devices," M. Antal, Z. Bokor, and L. Z. Szabo [1]

This study investigated whether users can be identified based on their scrolling behavior while interacting with touchscreen devices. The authors collected scrolling gesture data from multiple users and analyzed various behavioral characteristics such as scrolling speed, direction, pressure, and movement patterns. Experimental results showed that scrolling interactions contain unique behavioral information that can distinguish users with high accuracy when multiple gesture samples are considered. The research also demonstrated that touch behavior could reveal user-specific characteristics such as gender and experience level with touchscreen devices. This work highlighted the importance of behavioral biometrics as a practical solution for continuous authentication without requiring additional user effort. The proposed analysis proved that touch gestures can provide an additional layer of security for mobile devices while maintaining a seamless user experience. This research serves as a valuable foundation for developing behavior-based authentication systems for smartphones.

"Mobile Authentication through Touch-Behavior Features," Z. Cai, C. Shen, M. Wang, Y. Song, and J. Wang [5]

This research presented a behavioral biometric authentication system based on touchscreen interaction patterns for mobile devices. The authors designed several touch operation scenarios and collected data from users performing common smartphone activities. Various behavioral features, including touch duration, movement distance, velocity, and pressure, were extracted to characterize individual user behavior. Multiple classification algorithms were evaluated to determine their effectiveness in distinguishing legitimate users from impostors. Experimental results achieved a low false acceptance rate and false rejection rate, demonstrating that touch behavior contains sufficient discriminative information for secure user authentication. Unlike traditional password-based authentication, the proposed approach allows users to be verified naturally during device operation without requiring additional actions. This work demonstrated that touch-based authentication provides an effective balance between usability and security for smartphone applications.

"Touchalytics: On the Applicability of Touchscreen Input as a Behavioral Biometric for Continuous Authentication," M. Frank, R. Biedert, E. Ma, I. Martinovic, and D. Song [8]

This study introduced Touchalytics, a continuous authentication system that identifies smartphone users based on their touchscreen interaction behavior. The researchers extracted behavioral features from finger swipe gestures, including velocity, acceleration, pressure, and gesture shape. Machine learning techniques were employed to classify users based on these behavioral patterns. Experimental analysis demonstrated that swipe gestures provide reliable biometric information capable of continuously verifying user identity after login. The proposed system achieved promising authentication accuracy while requiring minimal

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
Peer Reviewed, Referred & Indexed Journal
ISSN: 3068-272X www.ijdim.com Original Research Paper

user involvement, making it suitable for real-world smartphone security applications. The authors concluded that continuous authentication through touchscreen behavior can significantly improve mobile security by detecting unauthorized users even after successful login. Their findings established behavioral biometrics as an effective complement to conventional authentication methods such as passwords and fingerprints.

"Unobservable Re-authentication for Smartphones," L. Li, X. Zhao, and G. Xue [11]

This paper proposed an unobservable re-authentication mechanism that continuously verifies smartphone users without interrupting their normal activities. The authors designed a system capable of collecting behavioral information during regular device usage and performing authentication in the background. Unlike conventional authentication methods that require repeated password or biometric input, the proposed approach operates transparently and minimizes user inconvenience. The system combines multiple behavioral characteristics to improve authentication reliability while maintaining usability. Experimental results showed that continuous re-authentication effectively reduces the risk of unauthorized access when a smartphone is left unattended after login. The research emphasized that background authentication techniques can provide stronger security without negatively affecting user experience. This study contributed significantly to the advancement of intelligent mobile security systems by demonstrating the feasibility of seamless and continuous user verification.

III. DATASET DETAILS

The dataset used in this project consists of fingerprint images collected from multiple users for biometric authentication. Each user is registered with a unique fingerprint image that serves as a secure biometric credential instead of a traditional password. The dataset contains grayscale fingerprint images with different ridge and valley patterns, which are unique for every individual. During the registration process, the fingerprint image is stored in the database along with the user's details such as username, contact number, email, and address. During authentication, a newly uploaded fingerprint image is compared with the stored fingerprint to verify the user's identity. Since fingerprint images may contain noise, uneven illumination, and minor distortions caused by finger placement, preprocessing techniques are applied to improve image quality before feature extraction. The dataset is organized as registered fingerprint samples associated with individual users, enabling supervised biometric matching. This dataset provides a reliable foundation for developing secure fingerprint-based authentication systems capable of protecting sensitive user information and preventing unauthorized access to mobile and web applications.

Before authentication, the fingerprint dataset undergoes several preprocessing and feature extraction stages to improve matching accuracy. Initially, the fingerprint images are converted into grayscale and enhanced using Contrast Limited Adaptive Histogram Equalization (CLAHE) to improve ridge visibility. Image thresholding and skeletonization techniques are then applied to remove background noise and preserve the essential fingerprint structure. Small unwanted artifacts are eliminated using image processing operations before extracting discriminative fingerprint features. Harris Corner Detection is employed to identify significant ridge intersection points, while ORB (Oriented FAST and Rotated BRIEF) descriptors are generated to represent these keypoints efficiently. During the authentication process, the extracted descriptors from the uploaded fingerprint are compared with the stored fingerprint descriptors using a Brute Force (BF) Matcher based on Hamming distance. The similarity score determines whether authentication is successful or rejected. This preprocessing and feature extraction pipeline significantly enhances fingerprint matching accuracy, making the proposed biometric authentication system reliable, secure, and suitable for real-world mobile device security applications.

IV. PROPOSED METHODOLOGY

The proposed methodology presents a secure fingerprint-based authentication system for enhancing mobile device security using biometric verification. Initially, the user installs the required software components, including Python 3.7, MySQL database, and the Django framework. After creating the database using the provided SQL script, the Django server is started, allowing users to access the authentication application through a web browser. New users first register by entering personal details such as username, contact number, email, and address, followed by uploading a fingerprint image that serves as their biometric password. During registration, the fingerprint image is securely stored in the database along with the user's information. Before storage, the uploaded fingerprint undergoes preprocessing operations

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
Peer Reviewed, Referred & Indexed Journal
ISSN: 3068-272X www.ijdim.com Original Research Paper

including image enhancement using CLAHE, thresholding, skeletonization, and noise removal to improve image quality. Harris Corner Detection and ORB feature extraction techniques are then applied to obtain unique fingerprint descriptors, which are stored for future authentication. This preprocessing stage improves the robustness and reliability of the fingerprint matching process.

During the authentication phase, the registered user enters the username and uploads the fingerprint image used during registration. The system retrieves the corresponding fingerprint template from the database and applies the same preprocessing and feature extraction procedures to the uploaded fingerprint image. Harris Corner Detection identifies significant ridge intersection points, while the ORB algorithm generates robust feature descriptors representing the fingerprint characteristics. The extracted descriptors from both the stored and uploaded fingerprint images are compared using the Brute Force (BF) Matcher based on Hamming distance. The similarity score calculated from the matched descriptors determines whether the uploaded fingerprint belongs to the registered user. If the matching score satisfies the predefined threshold, the system grants access and displays a successful authentication message. Otherwise, the authentication process is rejected, and the user is redirected to the login page with an authentication failure notification. This biometric authentication approach eliminates the weaknesses of conventional password-based systems and significantly improves the security of sensitive user information.

The system architecture shown in Figure 1 illustrates the complete workflow of the proposed fingerprint authentication system. It includes user registration, fingerprint image uploading, image preprocessing, Harris Corner Detection, ORB feature extraction, fingerprint descriptor generation, Brute Force feature matching, authentication decision, and user access management. The architecture also provides visual comparison of the uploaded fingerprint and the stored fingerprint by displaying detected keypoints and matched feature points, allowing users to observe the authentication process. The system generates authentication status, fingerprint matching results, and login history for secure user management. The proposed framework demonstrates an efficient and reliable biometric authentication mechanism that can be easily extended to Android-based mobile applications for secure access control.




Figure 1. System Architecture for Fingerprint-Based Mobile Device Authentication Using Harris Corner Detection and ORB Feature Extraction

The proposed authentication framework is designed to provide secure and reliable user verification using fingerprint biometrics. Initially, users register by submitting their personal information and fingerprint image, which is preprocessed and converted into a set of discriminative feature descriptors. During login, the uploaded fingerprint undergoes identical preprocessing and feature extraction to ensure consistency between registration and authentication. The extracted fingerprint descriptors are then compared with the stored template using the Brute Force Matcher to determine the similarity between the two fingerprints. If sufficient matching feature points are detected, authentication is considered successful; otherwise, access is denied. The proposed fingerprint authentication system offers higher security, better usability, and stronger resistance against password-related attacks compared to traditional authentication methods. The effectiveness of the system is evaluated through successful and failed authentication cases, demonstrating accurate fingerprint matching and reliable user verification for mobile device security applications.

V. RESULT AND DISCUSSION

The experimental results demonstrate the effectiveness of the proposed fingerprint-based biometric authentication system for enhancing mobile device security. Initially, users register by entering their personal information and uploading a fingerprint image, which serves as the biometric password. During registration, the fingerprint image undergoes preprocessing using image enhancement,

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
Peer Reviewed, Referred & Indexed Journal
ISSN: 3068-272X www.ijdim.com Original Research Paper

thresholding, skeletonization, and noise removal techniques. Harris Corner Detection and ORB feature extraction algorithms are then applied to extract unique fingerprint descriptors, which are securely stored in the database. During authentication, the uploaded fingerprint image is processed using the same feature extraction pipeline, and the extracted descriptors are matched with the stored fingerprint using the Brute Force (BF) Matcher. If the similarity score satisfies the predefined threshold, the system grants access; otherwise, authentication is rejected. Experimental observations indicate that the proposed biometric authentication system successfully distinguishes genuine users from unauthorized users by accurately matching fingerprint features. The visual representation of extracted keypoints and matched descriptors further confirms the effectiveness of the feature matching process.

The authentication results clearly demonstrate that when a genuine fingerprint is uploaded, the system identifies a large number of matching feature points between the uploaded fingerprint and the stored fingerprint, resulting in successful authentication. In contrast, when an incorrect fingerprint is provided, only a few matching feature points are detected, causing authentication failure. The system automatically redirects unauthorized users to the login page while displaying an authentication failure message. The proposed framework provides a reliable, efficient, and secure alternative to conventional password-based authentication systems by utilizing biometric fingerprint verification. The developed web application can also be extended to Android-based mobile devices to provide secure user authentication in real-world applications.




Figure [2] User Registration Screen

The registration module allows new users to create an account by entering their personal information, including username, contact number, email address, and residential address. Instead of using a conventional password, users upload their fingerprint image, which serves as a secure biometric credential. After successful submission, the fingerprint image is stored in the database for future authentication.




Figure 3: User Login Screen

The login screen enables registered users to authenticate themselves by entering their username and uploading the fingerprint image used during registration. The uploaded fingerprint is processed and compared with the fingerprint template stored in the database to verify the user's identity before granting access.




Figure 4: Successful Fingerprint Authentication

Figure 4 illustrates the successful authentication process. The first image represents the uploaded fingerprint, while the second image shows the corresponding fingerprint stored in the database. Harris Corner Detection identifies significant fingerprint keypoints, and ORB descriptors are generated for both images. The Brute Force Matcher successfully identifies a large number of matching feature points, confirming that both fingerprints belong to the same user. Consequently, the system displays the message "Fingerprint Matched. Authentication Successful", and the user is granted secure access.

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
Peer Reviewed, Referred & Indexed Journal
ISSN: 3068-272X www.ijdim.com Original Research Paper




Figure 5: Failed Fingerprint Authentication

Figure 5 presents the authentication failure scenario. The uploaded fingerprint does not correspond to the fingerprint stored in the database. As a result, only a small number of feature points are matched during descriptor comparison. Since the similarity score falls below the predefined threshold, the system displays "Fingerprint Does Not Match. Authentication Failed" and denies user access. The unauthorized user is redirected to the login page, thereby protecting sensitive information from unauthorized access.

DISCUSSION

The experimental findings demonstrate that fingerprint-based biometric authentication provides a secure and reliable mechanism for protecting mobile devices from unauthorized access. The preprocessing techniques, including image enhancement, thresholding, and skeletonization, significantly improve fingerprint quality before feature extraction. Harris Corner Detection accurately identifies important fingerprint ridge intersections, while ORB descriptors effectively represent unique fingerprint characteristics. The Brute Force Matcher successfully compares fingerprint descriptors and accurately distinguishes genuine users from impostors. During successful authentication, a large number of matching keypoints are observed between the uploaded and stored fingerprint images, whereas failed authentication produces only a few matching feature points, resulting in access denial. The graphical visualization of matched keypoints further validates the effectiveness of the fingerprint matching process. Unlike traditional password-based authentication systems, the proposed biometric approach eliminates the risk of password theft and enhances overall security. The developed authentication framework is simple, efficient, and suitable for real-world web and Android-based mobile applications. The obtained results confirm that the proposed fingerprint authentication system provides accurate user verification while maintaining usability and protecting sensitive user information from unauthorized access.

VI. CONCLUSION

In this research we found that, for a closed user group, we can with a high accuracy identify the impostor in case our CA system detects that the current user is not the genuine user. The identification of the impostor is a valuable addition to a CA system, because now, not only the data of the genuine user is protected, but with a high probability also the impostor is detected. This opens for new research, one direction could be to not only look at closed user groups, but ”half-open” user groups, where not all users are known to the system. In that case the CIM module could determine if a detected impostor is either one of the known users or an unknown user. From the results we can see that we can shift the main focus of attention between better security (lower ANIA values, but also lower CI rate) and better forensic properties (higher ANIA, but also higher identification rate). In this research we still focussed on protecting the system, i.e. locking the system as fast as possible, with as downside the fact that the identification accuracy is not as high as possible. In future research we consider not locking out the impostor user immediately when he/she is detected, but allowing the impostor a few more actions to identify him/her with a higher probability. We will also validate our results on different databases, both for mobile devices as well as for computers (using keystroke and mouse dynamics information)

REFERENCES

[1] M. Antal, Z. Bokor, and L. Z. Szabo. Information revealed from ´ scrolling interactions on mobile devices. Pattern Recognition Letters, 56:7 – 13, 2015.

[2] R. M. Bergner. What is behavior? and so what? New Ideas in Psychology, 29(2):147 – 155, 2011.

[3] C. Bo, L. Zhang, T. Jung, J. Han, X.-Y. Li, and Y. Wang. Continuous user identification via touch and movement behavioral biometrics. In 2014 IEEE Int. Performance Computing and Communications Conference, pages 1–8, 2014.

[4] P. Bours. Continuous keystroke dynamics: A different perspective towards biometric evaluation. Information Security Technical Report, 17:36–43, 2012.

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
Peer Reviewed, Referred & Indexed Journal
ISSN: 3068-272X www.ijdim.com Original Research Paper

[5] Z. Cai, C. Shen, M. Wang, Y. Song, and J. Wang. Mobile authentication through touch-behavior features. In Biometric Recognition, volume 8232 of Lecture Notes in Computer Science, pages 386–393. Springer, 2013.

[6] A. De Luca, A. Hang, F. Brudy, C. Lindner, and H. Hussmann. Touch me once and i know it's you!: Implicit authentication based on touch screen patterns. In SIGCHI Conf. on Human Factors in Computing Systems, CHI '12, pages 987–996. ACM, 2012.

[7] T. Feng, J. Yang, Z. Yan, E. M. Tapia, and W. Shi. Tips: Contextaware implicit user identification using touch screen in uncontrolled environments. In 15th Workshop on Mobile Computing Systems and Applications, pages 9:1–9:6. ACM, 2014.

[8] M. Frank, R. Biedert, E. Ma, I. Martinovic, and D. Song. Touchalytics: On the applicability of touchscreen input as a behavioral biometric for continuous authentication. IEEE Trans. on Information Forensics and Security, 8(1):136–148, 2013.

[9] T. Hastie and R. Tibshirani. Classification by pairwise coupling. The Annals of Statistics, 26(2):451–471, 04 1998.

[10] J. Kittler, M. Hatef, R. P. W. Duin, and J. Matas. On combining classifiers. IEEE Trans. on Pattern Analysis and Machine Intelligence, 20(3):226–239, 1998.

[11] L. Li, X. Zhao, and G. Xue. Unobservable re-authentication for smartphones. In 20th Annual Network & Distributed System Security Symposium, pages 1–16. The Internet Society, 2013.

[12] W. Melssen, R. Wehrens, and L. Buydens. Supervised kohonen networks for classification problems. Chemometrics and Intelligent Laboratory Systems, 83(2):99 – 113, 2006