
ZIGBEE BASED INTELLIGENT COAL MINE SAFETY HELMET SYSTEM

Sri K SUBRAHMANYAM¹, KATARI ANDRUS², KODAMALA SUMANTH BABU³, THUMATI RAJASEKHAR⁴, PATAN AHMED ALI KHAN⁵, MADDIBOYINA SOMA SEKHARA RAO⁶, KARI KRISHNA CHAITHANYA⁷.

¹ Assistant Professor, Department of CSE- IOT, St. Ann's College of Engineering & Technology, Chirala, Andhra Pradesh, India-523187.

²⁻⁷ UG Student, Department of CSE- IOT, St. Ann's College of Engineering & Technology, Chirala, Andhra Pradesh, India-523187.

ABSTRACT

The Integration of ZigBee wireless sensor networks in coal mine safety systems represents a transformative approach to addressing the persistent dangers inherent in underground mining operations. This implementation leverages ZigBee's low-power, mesh networking capabilities to create a comprehensive monitoring infrastructure that continuously tracks critical environmental parameters including methane concentrations, carbon monoxide levels, oxygen depletion, and structural integrity throughout the mine. By strategically deploying interconnected sensor nodes that maintain communication even when individual nodes fail, the system provides real-time data transmission to surface monitoring stations, enabling immediate detection of hazardous conditions and facilitating rapid emergency response. The self-organizing and self-healing nature of ZigBee networks ensures robust performance in the challenging underground environment, while battery-efficient operation allows for extended deployment without frequent maintenance. This technology not only enhances regulatory compliance but substantially improves worker safety through automated early warning systems, precise localization of personnel during emergencies, and data-driven insights that can inform preventative safety measures, ultimately reducing accident rates and potentially saving lives in one of the world's most hazardous industrial environments.

KEYWORDS:

Zigbee, Wireless Transmission Network, Temperature ,Humidity, Heart Beat, Liquid Crystal Display , Buzzer

1. INTRODUCTION

1.1 INTRODUCTION:

The evolution of coal mine safety helmets represents one of the most significant advances in miner protection, transforming from basic leather caps of the 19th century to sophisticated safety devices engineered with advanced materials science and digital technology. Modern helmets utilize high-grade polymers including reinforced fiberglass, carbon fiber composites, ABS, polycarbonate, and HDPE, each offering distinct advantages in impact dissipation, weight, and cost-effectiveness while

meeting stringent regulatory standards. The development trajectory has been driven by a growing understanding of underground hazards and increasingly stringent safety regulations established after devastating mining disasters throughout history.

Contemporary safety helmets serve as comprehensive safety hubs, integrating multiple protection systems including lighting, communication devices, respiratory protection connections, and attachments for face shields and hearing protection. These helmets must comply with strict international standards requiring rigorous

testing for impact attenuation, penetration resistance, electrical insulation, flammability characteristics, and performance under extreme temperatures. Industry experts continually refine these standards to address emerging threats and incorporate new protective capabilities as mining operations extend into more challenging environments and greater depths.

The digital transformation of mining operations has introduced "smart helmets" that incorporate environmental monitoring sensors to detect hazardous gases, oxygen depletion, and particulate matter concentration, providing immediate alerts when dangerous conditions emerge. Advanced models also feature biometric monitoring capabilities that track wearer health metrics including core temperature, heart rate variability, and fatigue indicators, enabling proactive intervention when miners show signs of physiological distress. These technological innovations represent a paradigm shift from passive protection to active hazard monitoring and prevention, fundamentally changing the relationship between miners and their safety equipment.

Modern mining helmets frequently incorporate sophisticated communication systems, including two-way voice communication, emergency notification buttons, and location tracking via RFID or other positioning technologies, proving particularly valuable during emergencies when standard communication infrastructure may be compromised. Enhanced visibility systems go beyond basic illumination to include variable brightness controls, adjustable beam patterns, emergency strobe functionality, and battery management systems with remaining-time indicators. These integrated systems transform the helmet from isolated protection gear into a node in a comprehensive mine safety network, enabling coordination and situational awareness previously impossible in underground environments.

Despite their clear safety benefits, implementing advanced helmet technologies presents challenges including significant costs, durability concerns in harsh mining environments, battery life limitations, and the need for comprehensive training programs to ensure proper use and overcome resistance to new technologies. Mining operations in developing regions face particular challenges in balancing advanced safety features against economic constraints, often necessitating phased implementation approaches and creative financing solutions to achieve necessary safety improvements without threatening operational viability. Regulatory frameworks increasingly require minimum technology standards while providing incentives for adoption of advanced safety features.

Mining has historically ranked among the most hazardous occupations worldwide, with coal mining presenting particularly severe risks to worker safety. Throughout mining history, head injuries have constituted a significant portion of mining-related casualties and injuries. The evolution of safety helmets in coal mining represents one of the most fundamental advances in miner protection technology, transforming from rudimentary leather caps to sophisticated multi-functional protective devices.

In the early days of coal mining, workers entered hazardous underground environments with minimal protection. The first dedicated mining helmets emerged in the late 19th century, consisting primarily of hardened leather constructions that offered nominal protection against minor impacts. These early designs, while representing progress, provided insufficient defense against major rock falls, machinery accidents, and other serious hazards prevalent in mining operations.

The transition to hard helmets began in the early 20th century, with the introduction of metal helmets providing improved impact resistance. However, these metal constructions introduced their own hazards, particularly in environments with electrical

equipment. The subsequent development of non-conductive materials, particularly reinforced plastics and composites in the mid-20th century, marked a revolutionary advancement in miner protection.

1.2 PROBLEM STATEMENT

Underground coal mining operations remain among the most hazardous occupational environments globally, with miners facing constant threats from toxic gas accumulation including carbon monoxide and methane, oxygen depletion in confined spaces, catastrophic structural collapses, explosions triggered by flammable gas ignition, equipment failures in harsh conditions, and communication blackouts that prevent emergency coordination when disasters occur. Traditional wired monitoring systems in mines suffer from infrastructure vulnerability to collapses and explosions that sever communication cables precisely when emergency alerts are most critical, while the extensive cabling requirements make comprehensive sensor deployment economically prohibitive and logistically impractical in vast underground tunnel networks spanning kilometers. Existing safety protocols rely heavily on periodic manual inspections and portable gas detectors carried by miners, creating dangerous gaps in monitoring coverage where hazardous conditions can develop undetected between inspection intervals, while individual miners lack real-time awareness of evolving threats in remote tunnel sections until conditions reach immediately life-threatening levels. The absence of real-time environmental monitoring infrastructure prevents early detection of gradual gas accumulation, temperature increases indicating underground fires, or structural stress patterns preceding collapses, eliminating opportunities for preventive evacuation before catastrophic events occur. Communication limitations in underground environments where conventional radio frequencies cannot penetrate rock formations leave miners isolated without reliable means to report emergencies, request

assistance, or receive evacuation instructions during critical incidents when coordination could mean the difference between survival and tragedy. The lack of integrated monitoring systems that track both environmental hazards and miner locations prevents rescue teams from efficiently locating trapped personnel during post-accident search operations, significantly reducing survival probabilities as critical hours elapse. Worker fall detection capabilities are virtually nonexistent in current mining safety infrastructure, meaning that miners who lose consciousness from gas exposure, suffer injuries from falls or equipment accidents, or become incapacitated in remote tunnel sections may remain undiscovered for extended periods until their absence is noted during shift changes or routine checks. These interconnected safety deficiencies result in thousands of preventable mining fatalities annually worldwide, with the majority occurring in developing nations where economic pressures discourage investment in comprehensive safety infrastructure despite well-established technological solutions. The challenge demands affordable, robust, wireless monitoring systems that provide real-time environmental sensing, reliable underground communication, automatic emergency detection, and comprehensive data integration to transform mine safety from reactive disaster response to proactive hazard prevention through continuous situational awareness for both miners and surface monitoring stations.

1.3 OBJECTIVES OF THE PROJECT

The primary objectives of this project are: To design and implement a comprehensive wireless sensor network utilizing Zigbee communication protocol that enables real-time monitoring of critical environmental parameters including carbon monoxide concentration, methane levels, oxygen availability, temperature, humidity, and structural vibrations throughout underground coal mine tunnel networks without vulnerable wired infrastructure

susceptible to damage during collapses or explosions. To develop distributed sensor nodes based on Arduino microcontrollers that acquire data from CO sensors detecting toxic gas accumulation, DHT11 modules measuring temperature and humidity conditions, vibration sensors identifying structural instability or equipment malfunctions, and fall detection MEMS accelerometers recognizing worker accidents or incapacitation events requiring immediate emergency response. To establish reliable underground wireless communication infrastructure using Zigbee mesh networking that maintains connectivity even when individual nodes fail or are destroyed, with automatic route reconfiguration ensuring continuous data flow from deep tunnel sections to surface monitoring stations despite the challenging propagation environment and physical obstacles inherent in mining operations. To create centralized monitoring and control systems based on ESP32 platforms at surface stations that aggregate sensor data from distributed underground nodes, analyze trends to predict developing hazards before they reach critical thresholds, display real-time conditions on LCD interfaces for operator awareness, and trigger multi-channel alerts through buzzers, visual indicators, and IoT cloud notifications when dangerous conditions are detected. To implement automated emergency response protocols that activate upon detection of gas threshold violations, abnormal temperature spikes, significant vibration events, or worker fall incidents, immediately alerting both underground personnel through local warning devices and surface emergency response teams through IoT connectivity with precise location information for rapid intervention. To develop IoT integration capabilities that transmit mining safety data to cloud platforms for remote monitoring by management, regulatory compliance documentation, historical trend analysis supporting predictive maintenance and hazard forecasting, and emergency notification to external rescue services when on-site response capacity is exceeded. To validate system performance through

comprehensive testing that measures sensor accuracy across expected environmental ranges, Zigbee communication reliability and latency under various underground conditions, fall detection sensitivity and specificity, power consumption for battery-powered nodes requiring extended operational duration between maintenance interventions, and overall system effectiveness in detecting and alerting to simulated emergency scenarios representative of actual mining hazards.

2. LITERATURE SURVEY

1. Li, M., & Liu, Y. (2019): "Wireless Sensor Network Deployment Strategies for Underground Coal Mine Monitoring Applications." *Journal of Network and Computer Applications*, 145, 102-118. Investigated optimal sensor placement algorithms and network topology configurations for maximizing coverage while minimizing node count in tunnel environments, demonstrating that mesh networks achieve 95% reliability with 40% fewer nodes compared to star topologies, providing practical deployment guidelines for cost-effective comprehensive monitoring.

2. Zhang, X., & Wang, H. (2020): "Zigbee Protocol Performance Analysis in Underground Mining Communication Environments." *Wireless Networks*, 26(7), 4823-4837. Evaluated Zigbee transmission characteristics including packet loss rates, latency, and throughput in simulated underground conditions with varying rock compositions, humidity levels, and interference sources, establishing that 2.4 GHz Zigbee maintains acceptable performance at ranges up to 80 meters between nodes with strategic repeater placement extending total network coverage indefinitely.

3. Kumar, S., & Patel, R. (2018): "Real-Time Carbon Monoxide Detection Systems for Mining Safety Using Electrochemical Sensors." *Sensors and Actuators B: Chemical*, 273, 456-468. Developed calibration procedures and temperature

compensation algorithms for electrochemical CO sensors in mining applications, achieving detection accuracy of ± 3 ppm across 0-1000 ppm measurement range with response times under 30 seconds suitable for early warning before concentrations reach immediately dangerous levels.

4. Anderson, T. J., & Brown, K. L. (2021): "MEMS Accelerometer-Based Fall Detection Algorithms for Worker Safety Monitoring in Industrial Environments." *IEEE Sensors Journal*, 21(12), 13456-13468. Proposed machine learning classification approaches distinguishing actual falls from normal activities and equipment vibrations using tri-axial acceleration patterns, achieving 94% detection sensitivity with false alarm rates below 2% through threshold optimization and temporal feature extraction from acceleration magnitude and vector angle changes.

5. Chen, W., & Zhou, T. (2019): "Mesh Networking Protocols for Reliable Data Transmission in Harsh Underground Industrial Environments." *IEEE Transactions on Industrial Informatics*, 15(8), 4512-4523. Analyzed routing algorithms, packet prioritization strategies, and redundancy mechanisms that maintain connectivity despite node failures or radio propagation obstacles, demonstrating that adaptive multi-path routing reduces message loss probability from 15% to less than 1% compared to single-path approaches in environments with 20% node failure rates.

3. PROPOSED SYSTEM

The proposed system, as illustrated in the block diagram, overcomes these limitations by integrating multiple sensors and communication modules into a single unit powered by an Arduino microcontroller. The system includes a vibration sensor, CO (carbon monoxide) sensor, DHT11 (for temperature and humidity), and a MEMS-based fall detection sensor. These sensors continuously monitor the environment and the user's physical condition. Data from these sensors is processed by the Arduino, which then transmits critical alerts through a Zigbee

transmitter for remote monitoring. Simultaneously, real-time data is displayed on an LCD screen, and an audible alert is triggered via a buzzer in case of anomalies. A regulated power supply ensures the stable operation of all components. This integrated and automated setup significantly enhances safety monitoring, real-time alerting, and communication efficiency, making it ideal for applications such as elderly care, worker safety, or environmental monitoring.




Fig.1.Block diagram

Zigbee Transmitter (Tx) – In the Arduino-Based Transmitter Unit

Location in Diagram: Right side of the Arduino block (first image)

◆ Function:

- The Zigbee Transmitter (Tx) module is connected to the **Arduino microcontroller**.
- It is responsible for **wirelessly sending sensor data** (from vibration, CO, temperature, humidity, and fall detection sensors) to a remote device.
- Operates on **IEEE 802.15.4 standard**, designed for low-power and low-data-rate communication, ideal for sensor networks.

◆ Role in the System:

- Collects processed data from the Arduino and transmits it to the **Zigbee Receiver** connected to the ESP32 in the remote monitoring unit.
- Ensures **real-time and wireless data transfer**, eliminating the need for wired communication between distant units.

Zigbee Receiver (Rx) – In the ESP32-Based Receiver Unit

Location in Diagram: Left side of the ESP32 block (second image)

◆ Function:


- The Zigbee Receiver (Rx) module is connected to the **ESP32 microcontroller**.
- It receives the sensor data wirelessly from the Zigbee Transmitter.
- Acts as the **entry point for all data** coming from the field sensor unit (Arduino system).

◆ Role in the System:

- Passes the received data to the ESP32 for further processing.
- The ESP32 then:
 - Displays the data on the LCD,
 - Activates alerts through the buzzer if needed,
 - Sends the data to an IoT platform for cloud-based monitoring.

This Zigbee link enables **wireless, low-cost, and reliable data transfer** between the sensor node and the remote monitoring unit, making it ideal for applications like industrial safety, healthcare, or home automation.

Circuit diagrams:



🔌 Power Supply Section

- **Step-down Transformer:** Reduces AC mains voltage (typically 230V) to a lower AC voltage.
- **Bridge Rectifier (D1–D4):** Converts AC to pulsating DC.
- **Filter Capacitors (1000µF & 100µF):** Smoothens the DC signal by reducing ripple.
- **Voltage Regulator (7805):** Regulates output to a constant +5V DC.
- **Indicator LED (with series resistor):** Confirms power is available.

This 5V output powers the ESP32 and all connected modules (LCD, Zigbee, buzzer, etc.).

ESP32 Microcontroller Section

- Acts as the **main controller** in the receiver unit.
- Interfaces with:
 - Zigbee Receiver Module
 - IoT Module
 - 16x2 LCD Display
 - Buzzer

ESP32 GPIO pins are used to receive signals and control output devices.

Zigbee-RX Module

- Connected to **GPIO 23** of ESP32.
- Receives data wirelessly from the transmitter (helmet unit with sensors).
- Sends this data to the ESP32 for further processing and display.

IoT Module

- Connected to **GPIO 15**.
- Used to send received sensor data to a **cloud platform** or remote server for real-time monitoring.
- Enables remote access to data, improving miner safety management.

16x2 LCD Display


- Connected to GPIOs (likely GPIOs 12 to 14, 25–27 based on typical LCD pin connections).
- Displays sensor values and alerts in real-time.
- Useful for local monitoring by supervisors or the miner themselves.

Buzzer Module

- Connected to **GPIO 17**.
- Triggers an **audible alert** in case of any hazardous condition detected (like gas leak or fall).
- Acts as an emergency response alert system.

Power Connections

- All modules (Zigbee, LCD, IoT, Buzzer) are powered by **regulated +5V** from the power supply section.
- Common ground is connected across all components to complete the circuit.



4. RESULTS




Fig 2 : overall Hardware Implementation




Fig 2: Zigbee Transmitter Circuit

5. CONCLUSION

In conclusion, the proposed coal mine safety helmet system significantly enhances worker safety through a two-tier architecture combining real-time sensing and wireless data transmission. The transmitter unit, built around an Arduino microcontroller, collects critical data such as vibration, carbon monoxide levels, temperature, humidity, and fall detection using various sensors, and transmits it wirelessly via Zigbee. The receiver unit, powered by the ESP32 microcontroller, receives this data through Zigbee and leverages IoT capabilities to display real-time information on an LCD, activate alarms through a buzzer, and send updates to a remote server for continuous monitoring. This integrated solution provides a robust and intelligent safety mechanism, ensuring timely alerts and effective response to hazardous conditions in coal mining environments.

REFERENCES

-
- [1] Dange, K.M., Patil, R.T. (2013), Design of Monitoring System for Coal Mine Safety Based on MSP430.
- [2] Toby Berger. Spatial direct reuse in remote sensor network[j]. Remote Network, 2008,14(2):133-146.
- [3] Dheeraj "IoT in burrowing for distinguishing, Monitoring and desire for underground mines Roof support", assembling on progressing information and progress development 2018
- [4] Dong "Coal Mine prosperity Monitoring system subject to Zigbee and GPRS ",Applied Mechanics and Material Volume 422,2013.
- [5] Tao Zhiyong, Li Xin. "Remote Temperature System Design Based on nRF905", Journal of Zhongguo Technology I mformation, 2007.22, p.53.
- [6] G. Dinardo, L. Fabbiano, and G. Vacca, "A smart and intuitive machine condition monitoring in the Industry 4.0 scenario," Meas. J. Int. Meas. Confed., 2018, doi: 10.1016/j.measurement.2018.05.041.
- [7] A. Pantelopoulos and N. G. Bourbakis, "A survey on wearable sensor-based systems for health monitoring and prognosis," IEEE Transactions on Systems, Man and Cybernetics Part C: Applications and Reviews. 2010, doi: 10.1109/TSMCC.2009.2032660.
- [8] A. Schütze, N. Helwig, and T. Schneider, "Sensors 4.0 - Smart sensors and measurement technology enable Industry 4.0," J. Sensors Sens. Syst., 2018, doi: 10.5194/jsss-7-359-2018.
- [9] WANG Longkanga, NIE Baishenga, ZHANG Ruminga, ZHAI Sheng Rui, LI Hailonga, "ZigBee-based positioning system for coal miners", SciVerse ScienceDirect, ELSEVIER, Vol. No : 26, Page: 2406-2414, 2011.
- [10] Bo Chengan, Xin Chengb, Junliang Chena, "Lightweight monitoring and control system for coal mine safety using REST style", ISA Transactions, ELSEVIER, Vol. No: 54, Page: 229-239, 2015.
- [11] Yaqin Wua, Mengmeng Chenb, Kai Wangb, Gui Fub, A dynamic information platform for underground coal mine safety based on Internet of Things, International Journal of Safety Science, ELSEVIER, Vol. No: 113, Page: 9-18, 2019.
- [12] Yingli Zhu, Guoping You, "Monitoring System for Coal Mine Safety Based on Wireless Sensor Network", Cross Strait Quad-Regional Radio Science and Wireless Technology Conference (CSQRWC), China, 2019.
- [13] Liang Dan, Yao Jun, "Application of IPv6 in Coal Mine Safety Production Monitoring", International Conference on Sensor Networks and Signal Processing, Page: 45-48, 2018.
- [14] Ivan Alfonso, Camilo Gómez, Kelly Garces, Jamie Chavarriaga, "Lifetime Optimization of Wireless Sensor Networks for Gas Monitoring in Underground Coal Mining", 7th International Conference on Computers Communications and Control (ICCCC), Page: 224-230, 2018.
- [15] Dingwei Li, Shuang Li, Mengjie You, "Research on mine safety situation prediction model : the case
-