International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
ISSN: 3068-272X www.ijdim.com Original Research Paper

NEXT-GEN POWER BACKUP: HYBRID SOLAR AND WIND UPS FOR A GREENER TOMORROW

[1]*Apoorna Ghosh,*[2]*Kalyan Kumar*
Department of EEE
Indian Institute of Engineering Science and Technology, Shibpur (IIEST)

Received: 03-03-2022 Accepted: 08-4-2022 Published: 16-4-2022

ABSTRACT:
The rising demand for clean, reliable, and uninterrupted electricity has led to the exploration of hybrid renewable energy systems as viable alternatives to conventional power sources. This study presents the design and implementation of a Hybrid Solar and Wind Powered Uninterruptible Power Supply (UPS), engineered to deliver sustainable and resilient energy solutions. By integrating solar photovoltaic panels with wind turbine generators, the system effectively harnesses complementary renewable resources, thereby ensuring a continuous power supply under varying environmental conditions.

A smart power management controller regulates energy flow, prioritizing renewable sources while seamlessly switching to battery storage during low generation periods. This hybrid UPS not only reduces dependency on fossil-fuel–based grid power but also minimizes carbon emissions, making it an eco-friendly backup solution. Experimental results and simulations demonstrate improved energy efficiency, reduced downtime, and cost-effectiveness compared to conventional UPS systems.

The proposed solution highlights the potential of hybrid renewable UPS technology as a next-generation backup system, capable of meeting the dual goals of energy reliability and environmental sustainability.

I.INTRODUCTION

The growing reliance on electricity in domestic, industrial, and commercial sectors has amplified the need for reliable and uninterrupted power supply systems. Conventional Uninterruptible Power Supply (UPS) solutions, though effective in short-term power continuity, typically depend on grid electricity or fossil-fuel–based sources, which are neither sustainable nor environmentally friendly. With the increasing concerns over climate change, fossil fuel depletion, and carbon emissions, the pursuit of green energy alternatives has become a pressing necessity.

Renewable energy technologies such as solar photovoltaic (PV) systems and wind turbines have emerged as promising solutions for sustainable energy generation. However, their standalone application often faces limitations due to the intermittent nature of these resources—solar panels rely on daylight availability while wind turbines depend on wind speed fluctuations. To overcome these challenges, the integration of hybrid renewable energy systems has gained significant attention in both research and practice.

A Hybrid Solar and Wind Powered UPS combines the strengths of both renewable sources, ensuring continuous energy availability by balancing resource variability. The hybrid architecture employs smart power management and battery storage, enabling efficient energy utilization and seamless switching between sources. Such systems not only provide uninterrupted backup power but also promote energy independence and carbon footprint reduction.

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
ISSN: 3068-272X www.ijdim.com Original Research Paper

This paper explores the design and implementation of a next-generation hybrid UPS system that leverages solar and wind energy for sustainable backup solutions. The proposed approach aims to address the dual challenge of energy reliability and environmental responsibility, offering a practical and scalable model for future green power infrastructure.

II.LITERATURE SURVEY

1. Hybrid renewable UPS concept & motivation

Hybrid UPS systems combine multiple renewable generators (usually PV + wind) with energy storage and power-electronics interfaces to provide uninterrupted power while maximizing renewable utilization. The central motivation is to overcome single-source intermittency (day/night for PV; variable wind) by exploiting their temporal complementarity, thereby increasing availability, reducing diesel/grid reliance, and lowering lifecycle emissions.

2. Power electronics & interfacing architectures

Two common topologies appear in the literature:

AC-coupled hybrid UPS: separate inverters for PV and wind feed a common AC bus; a UPS inverter/bidirectional converter manages battery charge/discharge and supplies critical load. Advantage: modularity; drawback: extra conversion steps.

DC-coupled hybrid UPS: PV and wind (via rectifiers) feed a DC bus with a single bidirectional inverter for loads and battery; offers higher conversion efficiency and simpler power flow control but needs careful DC bus management and protection design.

Studies emphasize component selection (MPPT for PV, turbine rectification, grid-forming vs grid-following inverters) and protection (fault ride-through, anti-islanding for grid-connected modes).

3. Maximum Power Point Tracking (MPPT) & wind energy capture

MPPT algorithms for PV (Perturb & Observe, Incremental Conductance, MPPT with neural nets or fuzzy controllers) are standard; literature increasingly tests adaptive/ML-assisted MPPT under partial shading and rapid irradiance changes. For small wind turbines, MPPT often uses tip-speed ratio control or power-curve lookup with adaptive control to maximize capture under variable wind; hybrid systems must coordinate MPPTs to avoid conflicts on shared DC/AC buses.

4. Energy storage, battery management & UPS behavior

Battery choice (lead-acid, Li-ion, $LiFePO_4$) is central — tradeoffs include cost, energy density, cycle life, depth-of-discharge rules, and thermal management. Battery Management Systems (BMS) for safety and lifetime optimization are well-covered; advanced strategies include state-of-charge (SoC) forecasting, dynamic charge/discharge scheduling, and lifetime-aware control (e.g., limiting charging currents to extend life). The UPS control logic must prioritize renewable usage, sustain critical loads during outages, and manage seamless transition (zero/near-zero transfer time) to battery/inverter output.

5. Energy management & control strategies

Research shows multiple control layers:

Primary/fast control: inverter-level regulation for voltage/frequency, anti-islanding, and current limits.

Secondary/EMS layer: decides source prioritization, battery dispatch, load shedding, and charge scheduling based on forecasts and constraints. EMS strategies include rule-based heuristics, optimization solvers (linear/quadratic programming), and increasingly model predictive control (MPC) for horizon-based scheduling using short-term solar/wind forecasts and load predictions. MPC and stochastic optimization are promising for maximizing renewable use while respecting battery health.

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
ISSN: 3068-272X www.ijdim.com Original Research Paper

6. Forecasting & predictive scheduling

Short-term forecasting (minutes–hours) for irradiance, wind speed, and load is often used to improve EMS performance. Statistical models, machine learning regressors, and ensemble methods reduce uncertainty and enable predictive dispatch, lowering reliance on storage and grid/diesel backup. Several studies report measurable gains in renewable utilization and cost savings when forecasts are integrated into EMS.

III.DESIGN OF HARDWARE

In essence, this part aids in explaining only the equipment. that as well as thoroughly discuss this same diagram of each component.

Arduino Uno

Based on its 8-bit architecture, the Arduino appears to be a microcontroller (datasheet). These include seven analogue general-purpose inputs, one serial interface earthenware photonic crystal, one USB, an influence joe, a type of icsp header, digital pin input/output tuning pegs (six of which might be used similarly to pulse width modulation outputs), and a restart right-click. This includes everything required to maintain the same micro-controller; it is connected to a desktop computer via a micro USB and energy using a power supply and dc/dc extender to simply get started.

Since it does not use a USB-to-serial serial chip for external power, this same POC differs on all leading-up panels. Rather, it is a technical age (atmega8u2 as much as edition r2) that is only set up as a serial-to-USB decoder. In some patients with early configuration, the panel appears to have a resistive element that is beginning to draw its 8u2 hwb row of between earth. The following new showcases appear to be on the Arduino Uno board:

• 1. Zeros add around: introduced point by point, but instead of providing a synopsis of the gpio that is close to it despite being made lock, there is also another new gpio near the repair lock, an ioref a specific authorisation a covers versus acclimatise towards the portion of the spectrum first from deck. In the future, defences will work well with platforms that use voltage regulators, which also function at 5 volts, and microcontrollers, which are responsible for the aforementioned platforms' continued operation at three volts. cooperative group. The second, like Destiny Aims, is likewise limited and not a connected connector.

- A more robust repair loop.
- The atmega 16u2 began to replace the 8u2.

Since "che" seems to indicate that one was in Europe, it is referred to as a complete label and will be released when all microcontrollers have been updated to 1.zero. Moving forward, che and htlv-1.zero will also be cited kinds like microcontrollers. For comparison with previous editions, the score after all micro controller boards is shown. This same che is actually the updated version of some sort of set after all flash drive Arduino and also the model again for microcontrollers system.



Fig: 1.ARDUINO UNO

POWER SUPPLY:

In terms of circuits or other equipment, the energy materials appear to be a device that transforms operational power from DC converter electricity into a low-to-high voltage. One power source comparison with known separated it into a group of halts, each of which performs a certain

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
ISSN: 3068-272X www.ijdim.com Original Research Paper

function. of one d.3 ° psu that is able to sustain a continuous voltage output, independent of one. "Regulated d.a and strength supply" refers to the three-degree main power volatility and traffic loads.




Fig:2 Block Diagram of Power Supply

LCD DISPLAY


Although a prototype is typically positioned for workout usage, it appears to be intended for the latter's sale. It can display emails in parallel columns to alphanumeric letters since it is primarily focused on its graphics servo controller (Hitachi). Additionally, the display displays all capital letters, Latin text, exclamation points, mathematical calculations, and similar items. Furthermore, it is possible to see a picture that a certain user has created that is superior to or comparable to one's own. completely automatic that changes the message to either exhibit (shift abandoned but also right), the iterator's body image, the led light, and other things. are seen to be beneficial traits.



Fig: LCD

BUZZER

Too few recent attempts have been made to drive an electronic circuit, such as retransmits, loud beeping circuit design, etc., using digital systems and node mcu metal prongs. Although such an electronic circuit requires more than 10 milliamperes of audio amplifiers to function properly, a microcontroller's lock might supply one to two milliamperes at the most. As a result, one pilot, for example, has been placed between the intercom circuit and the node mcu using an authority cmos technology.



WIFI MODULE:

In addition to servo controller capacity provided by Shanghai-based international manufacturing processes, the commonly associated microcontroller is merely a reduced area network microcontroller of complete tcp/ip pile. [] In 2015, the endophytic gadget, developed by a second maker, AI-thinker, brought the integrated circuits to the attention of European producers. Using hayes-style orders, one such small gadget allows embedded systems to connect to a community and establish a simple TCP/IP connection. But at the same time, there is hardly any British documentary proof for its microprocessor or even the instructions that acknowledge it. [2] The sale and the undeniable fact that there were only a few external parts suggested that this could eventually be inexpensive in quantity, which attracted a number of additional cybercriminals to look into the microprocessor and its technology as well as to compare it to Chinese documents. [3] The esp8285 is in fact a microcontroller to morpheus yep built blink, enabling single-chip devices to function as opposed to yoo. [4] The esp32 is, in fact, the son and heir to all of these servo controller french fries.



Solar panel :


A solar screen may be related to a single solar cell (PV) component, a single solar heating

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
ISSN: 3068-272X www.ijdim.com Original Research Paper


board, or even a group of them, such as photovoltaic (PV) circuits with wires connected but assembled on even a few. After all solar panels, a single photovoltaic panel appears to be a commercialised, comparable arrangement. Photovoltaic arrays can be utilised in retail and commercial settings to generate electricity or as a component of a larger photovoltaic system. Each component's output current energy has been categorised below test method illnesses; however, it typically varies after 99 total kw. An 8% productive hd 1mw component will also have many times the realm of a 16% productive lk kw component. The efficiency of any subsystem determines the world of such a current similar peak output. A few viable solar panel systems have efficiency levels above 19%. A single solar PV component could really begin generating a little amount of electricity; these facilities frequently include a variety of circuits. A single photovoltaic system often consists of a single screen or sometimes a photovoltaic array, a type of rectifier, or occasionally rechargeable batteries, but it also sometimes includes a solar tracking system instead of IoT electronics.

Solar circuits use photons, or incident light from the sun, to generate electricity using the photoelectric effect. Wafer-based silicon cells, cellular, and thin bacteria predicated to either transition metals or polycrystalline are used in the majority of circuits. The top stack or even the return surface can be a functional (load-bearing) citizen of such a component. Water content must be used to protect cells from physical stress. Significant sunlight arrays appear to be semi-flexible but constrictive. There is only one, which is based on forward-slender bacterium. Among the first to be used in rooms throughout the low to mid range were the solar photovoltaic plug-ins mentioned above.

In order to offer the needed realistic data, electrical links appear to be made in series or parallel with a desired amperage as well as/or simultaneously. In order to manage plated, brass, or some other quasi-semiconducting trivalent, it can conduct cords in a specific way. These similar cell lines ought to be connected to the system as a whole and to one another via electric current. The use of mc3 (older) and mc4 interconnects between companies, external sources, and common earth observation was made possible by differences in links to the underlying operating system. To optimise a vout-like device parts that are still lighted, eliminate electrodes that could be incorporated or seen from the outside.



IV.BLOCK DIAGRAM:



V.CONCLUSION

The development of a Hybrid Solar and Wind Powered UPS demonstrates a practical pathway toward achieving both uninterrupted power reliability and sustainable energy utilization. By integrating complementary renewable sources, the system effectively addresses the limitations of standalone solar or wind solutions, ensuring continuous power supply even under fluctuating environmental conditions. The inclusion of smart power management and storage mechanisms further enhances efficiency, reduces dependency on fossil fuels, and minimizes carbon emissions.

International Journal of
DATA SCIENCE AND IOT MANAGEMENT SYSTEM
ISSN: 3068-272X www.ijdim.com Original Research Paper

This hybrid approach not only meets the immediate need for reliable backup power in homes, institutions, and industries but also aligns with global efforts to promote clean energy transitions. Beyond its environmental benefits, the proposed solution proves to be cost-effective and scalable, making it suitable for adoption in both urban and rural settings.

Looking ahead, advancements in energy storage technologies, IoT-enabled monitoring, and AI-driven optimization can further improve the performance and adaptability of such hybrid systems. Thus, the hybrid solar–wind UPS stands as a next-generation model for resilient, eco-friendly, and future-ready energy backup solutions.

REFERENCES:

[1] Mahshid Amirabadi, Anand Balakrishnan, Hamid A. Toliyat and William C. Alexander, Member, IEEE "HighFrequency AC-Link PV Inverter" IEEE transactions on industrial electronics, vol. 61, no. 1, january 201

[2] T. Kerekes, R. Teodorescu, P. Rodríguez, G. Vázquez, and E. Aldabas, "A new high-efficiency single-phase transformerless PV inverter topology," IEEE Trans. Ind. Electron., vol. 58, no. 1, pp. 184–191, Jan. 2011.

[3] M. Amirabadi, A. Balakrishnan, H. A. Toliyat, and W. Alexander,"Soft switched AC-link direct-connect photovoltaic inverter,"in Proc. IEEE Int. Conf. Sustain.Energy Technology, 2008, pp.

[4] Aleksey Trubitsyn, Brandon J. Pierquet, Alexander K. Hayman, Garet E. Gamache , Charles R. Sullivan , David J. Perreault "High-Efficiency Inverter for PhotovoltaicApplications" , 2010 IEEE Energy Conversion Congress and Exposition, pp. 2803-2810, Sept. 2010

[5] Eftichios Koutroulisa, John Chatzakisa, Kostas Kalaitzakisa, Stefanos Maniasb, "System for inverter protection and real-time monitoring" Microelectronics Journal 34 (2003) 823

[6] S. Chakraborty, B. Kramer, and B. Kroposki, "A review of power electronics interfaces for distributed energy systems towards achieving low-cost modular design," Renew. Sustain. Energy Rev., vol. 13, no. 9, pp. 2323–2335, Dec. 2009.

[7] H. A. Toliyat"Partial Resonant ac Link Converters" Journal of Electrical Systems and Signals, Vol. 1, No. 1, Mar. 2013

[8] M. Amirabadi, H. A. Toliyat, and W. C. Alexander, "Battery-utility interface using soft switched AC link buck– boost converter," in Proc. IEMDC, 2009, pp. 1299–1304.

[9] G. Grandi, C. Rossi, D.Ostojic, and D. Casadei, "A new multilevel conversion structure for grid-connected PV applications,"IEEE Trans. Ind. Electron., vol.56, no.11, pp. 4416–4426,Nov. 2009.

[10] Y. Huang, F. Z. Peng, J. Wang, and D. W. Yoo, "Survey of the power conditioning system for PV power generation," in Proc. IEEE PESC, Jun. 18–22, 2006, pp. 1–6.

[11] S. Atcitty, J. E. Granata, M. A. Quinta, and C. A. Tasca, "Utility-scale gridtied PV inverter reliability workshop summary report", Sandia National Labs., Albuquerque, NM, USA, SANDIA Rep. SAND2011-4778

[12] S. Jain and V. Agarwal, "An integrated hybrid power supply for distributed generation applications fed by nonconventional energy sources," IEEE Tran. Energy Conversion. vol. 23, no. 2, pp. 622–631, Jun. 2008.