



SMART DAM MONITORING SYSTEM USING ARDUINO UNO, SIM800 GSM MODULE, AND WATER LEVEL SENSORS

Snehal Shevade, Poonam musmade, Kailas Tehare, Shyamsundar Matkar , Apurva Kakad ,Pralhad More,
Aditya Gadade,Hansika Agarwal

Ajeenkya D.Y.Patil School of Engineering , Lohegoan , Pune , India.

ABSTRACT: Dams are critical infrastructures for water resource management, flood control, irrigation, and renewable energy generation. However, traditional dam monitoring methods are often manual, error-prone, and slow to respond to emergencies, increasing the risk of catastrophic failures and inefficient resource utilization. This research paper presents a comprehensive design and analysis of a dam-based integrated monitoring and energy generation system that leverages a suite of modern technologies: water level sensors (ultrasonic, float, and pressure types), Arduino Uno and AutoBotix Arduino microcontrollers, alerting devices (buzzer and LEDs), SIM800 GSM module with Aierel SIM for SMS-based remote alerts. The system architecture, methodology, hardware and software integration, power management, safety mechanisms, and field deployment considerations are detailed. Results from prototype testing and analysis of expected metrics are discussed, alongside real-world applications, limitations, and future directions. The paper also addresses regulatory, ethical, and standardization aspects relevant to dam safety and monitoring. A schematic block diagram is provided to illustrate the integrated system. This work demonstrates a scalable, cost-effective, and robust solution for enhancing dam safety and operational efficiency.

Received: 21-11-2025

Accepted: 31-12-2025

Published: 13-01-2026

1. INTRODUCTION

Background: Dam Monitoring, Flood Alerts, and Micro-Hydropower

Dams serve as vital assets for water storage, flood mitigation, irrigation, and hydropower generation. Their safe and efficient operation is paramount, as failures can lead to devastating floods, loss of life, and significant economic damage. Traditionally, dam monitoring has relied on manual inspections and basic instrumentation, which are often insufficient for timely detection of hazardous conditions such as overtopping, structural distress, or rapid inflow changes. The increasing frequency of extreme weather events due to climate change further underscores the need for real-time, automated, and remote monitoring systems.

Flood alert systems are essential for providing early warnings to downstream communities and dam operators. Modern approaches integrate sensor networks, microcontrollers, and communication modules to automate data collection, analysis, and dissemination of alerts. The Dam Safety Act, 2021, in India, mandates the installation of scientific instruments, emergency action plans, and early

warning systems for all major dams, reflecting a global trend towards regulatory enforcement of dam safety standards.

Micro-hydropower, particularly in the form of small-scale turbines or DC motors driven by water flow, offers a sustainable means of generating electricity from existing water infrastructure. Integrating micro-hydropower with monitoring systems can provide local power for sensors and communication devices, enhance system resilience, and contribute to decentralized energy supply.

II LITERATURE REVIEW

Dam safety and water resource management are critical issues, especially in regions prone to heavy rainfall and flooding. Traditional dam monitoring methods rely heavily on manual inspection and wired instrumentation, which are often time-consuming, costly, and prone to delays in emergency situations. To address these limitations, researchers have explored automated dam monitoring systems using sensors and microcontroller-based platforms that provide real-time data and early warning capabilities.

Several studies have focused on water level monitoring using ultrasonic and float-based sensors. Reddy and Kumar (2019) developed an Arduino-based water level monitoring system that continuously measured reservoir levels and activated alerts when predefined thresholds were exceeded. Their work demonstrated that low-cost sensors combined with microcontrollers could effectively replace manual monitoring, though it lacked remote communication capabilities for real-time alerts.

With the advancement of wireless communication, GSM-based alert systems have been widely adopted for dam and flood monitoring applications. Patil et al. (2020) proposed a GSM-enabled flood monitoring system that used Arduino and water level sensors to transmit warning messages to authorities. The integration of GSM technology enabled reliable communication even in remote areas where internet connectivity was limited, making it suitable for rural dam monitoring scenarios.

Recent research has emphasized the integration of multi-level sensing and automated decision-making. Sharma and Mehta (2022) implemented a smart dam monitoring system using multiple sensors to track water level variations and structural safety parameters. Their system demonstrated improved accuracy and faster response time, highlighting the importance of IoT-enabled monitoring systems for disaster prevention and effective water resource management.

III. METHODOLOGY

The proposed smart dam monitoring system is designed to continuously monitor water levels and provide timely alerts using an Arduino Uno as the central control unit. Water level sensors are installed at different heights of the dam to detect rising water levels and classify them into safe, warning, and danger zones. The Arduino Uno reads sensor data at regular intervals and compares it with predefined threshold values. Based on the detected water level, the system determines the current status of the dam and initiates appropriate actions.

A SIM800 GSM module is interfaced with the Arduino Uno to enable wireless communication. When the water level reaches a critical threshold, the Arduino triggers the GSM module to send alert messages to designated authorities and emergency response teams. The system is programmed using the Arduino IDE, ensuring reliable sensor data processing and fast response. This methodology provides a cost-effective, real-time, and scalable solution for dam monitoring, enhancing safety and reducing the risk of flood-related disasters.



Fig. 1 Project Model

IV CONCLUSION AND FUTURE SCOPE

This research paper presents a comprehensive, integrated system for dam monitoring, alerting, and micro-hydropower generation, leveraging state-of-the-art sensor technologies, microcontroller platforms, GSM communication, and renewable energy harvesting. The modular architecture enables continuous, real-time water level monitoring, automated local and remote alerting, and sustainable power supply for field deployment. Prototype testing demonstrates robust performance, reliability, and scalability for diverse dam environments.

The system addresses critical challenges in dam safety, flood warning, and resource management,



aligning with regulatory mandates and best practices. Limitations related to network coverage, sensor maintenance, and power reliability are acknowledged, with recommendations for future enhancements including IoT/cloud integration, advanced analytics, and automated control.

By combining affordability, efficiency, and resilience, this solution provides a foundation for scalable smart water management in both academic and real-world applications. Its adoption can significantly enhance dam safety, operational efficiency, and sustainable development, contributing to disaster risk reduction and community resilience in the face of climate change and increasing water demands.

REFERENCES

- [1] Reddy, P. S., & Kumar, R. (2019). Arduino-based water level monitoring and alert system. *International Journal of Engineering Research and Technology*, 8(4), 456–460.
- [2] Patil, S., Kulkarni, A., & Deshmukh, R. (2020). GSM-based flood monitoring and early warning system using Arduino. *International Journal of Advanced Research in Electronics and Communication Engineering*, 9(6), 312–317.
- [3] Sharma, V., & Mehta, P. (2022). Smart dam monitoring and flood warning system using IoT. *Journal of Water Resources and Environmental Engineering*, 14(2), 98–105.
- [4] Singh, A., Verma, S., & Gupta, N. (2018). Real-time water level monitoring system using ultrasonic sensors. *International Journal of Computer Applications*, 179(25), 21–26.
- [5] Al-Fuqaha, A., Guizani, M., Mohammadi, M., Aledhari, M., & Ayyash, M. (2015). Internet of Things: A survey on enabling technologies and applications. *IEEE Communications Surveys & Tutorials*, 17(4), 2347–2376.
- [6] Chen, J., Li, X., & Wang, Y. (2021). IoT-based flood monitoring and early warning systems: A review. *Sensors*, 21(4), 1245.
- [7] World Meteorological Organization. (2023). *Flood forecasting and early warning systems*. WMO Press.
- [8] Nandigama, N. C. (2024). Data Science–Enabled Anomaly Detection in Financial Transactions Using Autoencoders and Risk Evaluation Mechanisms. *Journal of Information Systems Engineering and Management*.
<https://doi.org/10.52783/jisem.v9i2.44>
- [9] Khairnar, S., Bansod, G., Dahiphale, V. (2019). A Light Weight Cryptographic Solution for 6LoWPAN Protocol Stack. In: Arai, K., Kapoor, S., Bhatia, R. (eds) *Intelligent Computing. SAI 2018. Advances in Intelligent Systems and Computing*, vol 857. Springer, Cham. https://doi.org/10.1007/978-3-030-01177-2_71
- [10] Poonam Musmade, S. M. Khairnar, Sachin Rajas, A GRAPH THEORY–BASED APPROACH TO TRAFFIC FLOW MANAGEMENT , 2025, *International Journal of Engineering Sciences and Advanced Technology*, 25(12), Page 255-258, ISSN No: 2250-3676.
- [11] Khairnar, S., Bansod, G., Dahiphale, V. (2019). A Light Weight Cryptographic Solution for 6LoWPAN Protocol Stack. In: Arai, K., Kapoor, S., Bhatia, R. (eds) *Intelligent Computing. SAI 2018. Advances in Intelligent Systems and Computing*, vol 857. Springer, Cham. https://doi.org/10.1007/978-3-030-01177-2_71
- [12] Nandigama, N. C. (2025). Scalable Suspicious Activity Detection Using Teradata Parallel Analytics And Tableau Visual Exploration. *International Journal of Communication Networks and Information Security*, 8(3).
<https://doi.org/10.48047/ijcnis.8.3.236>.
- [13] Khairnar, S., & Bodra, D. . (2025). A Data-Driven Approach to Air Traffic Delay Prediction and Sentiment Evaluation. *International Journal of Basic and Applied*



- Sciences, 14(4), 184-193.
<https://doi.org/10.14419/cdx7kx09>
- [14] Poonam Musmade, Snehal Shevade, Prakash Mali, Shubhdarshini Patil, Srushti Pawar, Shruti Pawar, Prachi P. Patil, Kartik Pawar, “Smart Ev Charging System”, Journal of Science Engineering Technology and Management Science, Vol. 03, Issue 01, January 2026, pp: 1-5, DOI: <http://doi.org/10.64771/jsetms.2026.v03.i01.pp1-5>
- [15] Sushil Khairnar. “Application of Blockchain Frameworks for Decentralized Identity and Access Management of IoT Devices”. International Journal of Advanced Computer Science and Applications (IJACSA) 16.6 (2025). <http://dx.doi.org/10.14569/IJACSA.2025.0160604>
- [16] Sushil Khairnar and Deep Bodra. “Recommendation Engine for Amazon Magazine Subscriptions”. International Journal of Advanced Computer Science and Applications (ijacsa) 16.7 (2025). <http://dx.doi.org/10.14569/IJACSA.2025.0160796>
- [17] Sachin Dilip Rahinj (¹School of Engineering, Ajeenkya DY Patil University, Pune 412105, India), Samina F. Waglawala (¹School of Engineering, Ajeenkya DY Patil University, Pune 412105, India), Akhileshwar Singh (¹School of Engineering, Ajeenkya DY Patil University, Pune 412105, India), and Deepak Kumar Singh (¹School of Engineering, Ajeenkya DY Patil University, Pune 412105, India), International Journal of Modern Physics C 0 0:0