
SMARTEDGEFLOW: OPTIMIZED TRAFFIC CONTROL WITH CANNY EDGE DETECTION

¹Vamsi Krishna, ²Vedhika

Department Of Computer Science and Engineering

The George Washington University, Washington, D.C., United States

Received: 04-02-2023

Accepted: 08-03-2023

Published: 17-03-2023

ABSTRACT

Urban traffic congestion remains a significant challenge in modern cities, often exacerbated by traditional traffic management systems that rely on fixed timers or manual control. To address this issue, we propose SmartEdgeFlow, an intelligent traffic control system that leverages Canny Edge Detection to dynamically assess vehicle density and optimize signal timings in real time.

SmartEdgeFlow employs digital image processing techniques to analyze live traffic camera feeds. By detecting edges within the captured images, the system estimates the number of vehicles present at an intersection. The density of these edges correlates with traffic volume, enabling the system to adjust signal durations accordingly—allocating more green time to lanes with higher vehicle density and reducing it where traffic is lighter.

This approach offers several advantages over conventional methods:

Real-Time Adaptability: The system continuously processes live images, allowing for immediate adjustments to traffic signals based on current conditions.

Enhanced Efficiency: By optimizing signal timings in response to actual traffic volumes, SmartEdgeFlow reduces waiting times and improves overall traffic flow.

Scalability: The modular nature of the system allows for easy integration into existing traffic infrastructure without the need for extensive hardware modifications.

I. INTRODUCTION

Urban traffic congestion has become a critical challenge in cities worldwide, leading to increased travel times, elevated pollution levels, and diminished quality of life. In rapidly urbanizing regions, such as Patna, studies have highlighted issues like inadequate public transport, over-reliance on private vehicles, and rising pollution levels, with peak-hour speeds often dropping below 10 km/h.

Traditional traffic management systems often rely on fixed timers or manual control, which fail to adapt to real-time traffic conditions. This static approach contributes to inefficiencies, especially during peak hours or unexpected traffic surges.

To address these challenges, we propose SmartEdgeFlow, an intelligent traffic control system that utilizes Canny Edge Detection to dynamically assess vehicle density and optimize signal timings in real time. The

Canny Edge Detection algorithm, developed in 1986, is renowned for its ability to detect a wide range of edges in images, making it ideal for analyzing traffic camera feeds.

SmartEdgeFlow offers several advantages over conventional methods:

Real-Time Adaptability: Continuously processes live images, allowing immediate adjustments to traffic signals based on current conditions.

Enhanced Efficiency: Optimizes signal timings in response to actual traffic volumes, reducing waiting times and improving overall traffic flow.

Scalability: Easily integrates into existing traffic infrastructure without the need for extensive hardware modifications.

II. SYSTEM ANALYSIS

EXISTING SYSTEM:

Traditional traffic management systems primarily rely on two types of control mechanisms:

Fixed-Time (Pre-Timed) Control: This system operates on predetermined signal cycles, irrespective of real-time traffic conditions. It's commonly used in areas with consistent traffic patterns, such as downtown regions during off-peak hours.

Manual Control: In certain scenarios, traffic signals are manually operated by personnel, especially during peak hours or special events, to manage traffic flow.

Disadvantages of Existing Systems

While these traditional systems have been in use for years, they exhibit several limitations:

Inefficiency During Variable Traffic Conditions: Fixed-time systems do not adapt to fluctuations in traffic volume, leading to unnecessary delays and congestion. For instance, during off-peak hours, the system may continue to operate on a fixed cycle, causing vehicles to wait unnecessarily.

Vulnerability to Cyber-Tampering: Fixed-time systems can be susceptible to cyber-attacks, where malicious actors manipulate sensor data to disrupt traffic flow. Such vulnerabilities can compromise the safety and efficiency of the traffic management system.

Resource Intensive and Error-Prone Manual Control: Manual operation of traffic signals requires constant human intervention, which can lead to errors and inconsistencies. Additionally, it places a significant burden on human resources, especially during peak traffic times.

PROPOSED SYSTEM:

The proposed system, SmartEdgeFlow, introduces an advanced approach to urban traffic management by leveraging Canny Edge Detection to dynamically assess vehicle density in real time. Unlike traditional fixed-time or manual control systems, SmartEdgeFlow utilizes digital image processing techniques to analyze live traffic camera feeds, detecting edges that correspond to vehicle outlines. The density of these edges serves as an indicator of traffic volume,

allowing the system to adjust traffic signal timings accordingly.

This method offers several advantages over conventional traffic control systems:

Real-Time Adaptability: SmartEdgeFlow continuously processes live images, enabling immediate adjustments to traffic signals based on current traffic conditions. This dynamic response helps in reducing congestion and improving traffic flow.

Enhanced Efficiency: By optimizing signal timings in response to actual traffic volumes, the system minimizes waiting times and ensures a smoother flow of vehicles, leading to reduced fuel consumption and lower emissions.

Scalability and Integration: The modular nature of SmartEdgeFlow allows for easy integration with existing traffic infrastructure, making it a cost-effective solution for cities aiming to modernize their traffic management systems.

III. METHODOLOGY

The proposed SmartEdgeFlow system employs a multi-step approach to dynamically assess traffic density and optimize signal timings using the Canny Edge Detection algorithm. The methodology encompasses the following stages:

1. Image Acquisition

Traffic Camera Integration:

High-resolution traffic cameras are strategically placed at key intersections to capture real-time video feeds. These cameras provide continuous monitoring, ensuring up-to-date traffic data.

Preprocessing:

Captured frames are converted to grayscale to reduce computational complexity and focus on intensity variations essential for edge detection.

2. Edge Detection using Canny Algorithm

Gaussian Smoothing:

A Gaussian filter is applied to the grayscale image to smooth out noise, preserving important structural information.

Gradient Calculation:

The gradient magnitude and direction are computed using Sobel operators to identify areas of rapid intensity change, which correspond to edges.

Non-Maximum Suppression:

This step thins the edges by suppressing non-maximum gradient values, ensuring that only the most prominent edges are retained.

Double Thresholding:

Two threshold values are applied to classify edge pixels into strong, weak, and non-edges, allowing for better differentiation of actual edges from noise.

Edge Tracking by Hysteresis: Weak edges connected to strong edges are retained, while isolated weak edges are discarded, ensuring continuity in edge detection.

3. Vehicle Density Estimation

Edge Analysis: The processed edge-detected image is analyzed to count the number of edge pixels, which correlates with the number of vehicles present.

Density Calculation:

The ratio of edge pixels to total pixels in the region of interest is computed to estimate the vehicle density.

4. Traffic Signal Optimization

Signal Timing Adjustment: Based on the estimated vehicle density, the system adjusts the traffic signal timings. Higher density areas receive longer green light durations to alleviate congestion.

Real-Time Adaptation:

The system continuously updates signal timings in real-time, responding to changing traffic conditions and ensuring optimal flow.

5. System Integration and Deployment

Hardware Setup:

The system integrates with existing traffic signal hardware, utilizing microcontrollers or PLCs to control signal lights based on computed timings.

Software Interface:

A user-friendly interface is developed for monitoring system performance, allowing traffic management authorities to oversee operations and make manual adjustments if necessary.

Testing and Calibration:

Extensive testing is conducted to calibrate the system for different traffic scenarios, ensuring reliability and accuracy in various conditions

IV. RESULTS & DISCUSSIONS

1. Effectiveness of Traffic Density Estimation via Canny Edge Detection

Studies have shown that using Canny Edge Detection for vehicle density estimation leads to significant improvements in response time, automation, reliability, and overall efficiency compared to traditional fixed-time or manually-controlled systems. This is primarily because edge detection offers a reliable way to extract traffic information from CCTV feeds, measuring density through edge pixel analysis.

2. Performance Across Edge Detection Methods

The efficacy of Canny Edge Detection was compared against other popular edge detectors like Sobel, Roberts, and LOG. The findings revealed that, despite slightly higher processing time (~0.453 seconds per frame), Canny provided the most accurate and stable detection of vehicle outlines, confirming its suitability for smart traffic management systems.

3. Enhanced System Responsiveness and Efficiency

The real-time edge-based approach allows SmartEdgeFlow to dynamically adjust traffic signal timings based on actual traffic density, rather than relying on preset schedules. As a result, significant gains are achieved in throughput and reduction of wait times—empirical studies confirmed that more green time is allocated to denser lanes, optimizing flow across intersections.

4. Quality of Edge Detection Measured via Image Metrics

Canny-based systems outperform prior methods across various image quality metrics—including accuracy, entropy, PSNR, and MSE. These improvements ensure precise vehicle density measurement, which is crucial for dependable signal control decisions

V. CONCLUSION

This research introduces SmartEdgeFlow, an adaptive traffic control system that leverages Canny Edge Detection to dynamically assess vehicle density and optimize signal timings in real time. By analyzing edge pixels from CCTV feeds, the system ensures efficient management of traffic flow at critical intersections.

Empirical studies confirm that edge-based methods significantly outperform traditional timer-driven or manually controlled systems across multiple performance indicators—including accuracy, entropy, PSNR, MSE, reaction time, automation, reliability, and overall efficiency. The edge detection mechanism excels in extracting relevant traffic data from images, enabling rapid and precise decision-making.

Moreover, experimental comparisons highlight that Canny Edge Detection provides superior vehicle outline detection—even if slightly slower—compared to alternatives like Sobel and Roberts operators. These strengths translate into effective green signal allocation that is tailored to actual traffic conditions, leading to reduced congestion and improved traffic responsiveness.

REFERENCE

T. Tahmid and E. Hossain, “Density based smart traffic control system using canny edge detection algorithm for congregating traffic information,” in Proc. 3rd Int. Conf. Electrical Information and Communication Technology (EICT), Khulna, Bangladesh, Dec. 2017, pp. 1–5.

S. Ledalla, V. R. Gurram, G. K. P., S. Vodnala, M. M. Md, and R. R. Annapureddy,

“Density based smart traffic control system using canny edge detection algorithm along with object detection,” E3S Web Conf., vol. 391, Art. no. 01061, 2023.

P. Harsha, R. R. Rahatekar, T. Vaishnavi, and S. S. Reddy, “Density based smart traffic control system using canny edge detection,” Turkish J. Comput. Math. Educ. (TURCOMAT), vol. 15, no. 3, pp. 247–261, 2024.

D. V. Jilla, S. T. Srinivasulu, S. M. Poluri, L. K. Mynampati, and V. K. Kalla, “Density based smart traffic control system using canny edge detection algorithm for congregating traffic information,” Int. J. Mech. Eng. Res. Technol. (IJMERT), vol. 16, no. 1, pp. 152–161, Mar. 2024.

B. Lakshmipathi and P. Srujana, “Density based smart traffic control system using canny edge detection algorithm for congregating traffic information,” Int. J. Eng. Technol. Manage. Sci., vol. 7, no. 5, 2023.

K. Garg, S. K. Lam, T. Srikanthan, and V. Agarwal, “Real-time road traffic density estimation using block variance,” in Proc. IEEE Winter Conf. Applications of Computer Vision (WACV), 2016, pp. 1–9.

S. M. Uddin, A. K. Das, and M. A. Taleb, “Real-time area based traffic density estimation by image processing for traffic signal control system: Bangladesh perspective,” in Proc. Int. Conf. Electrical Engineering and Information Communication Technology (ICEEICT), 2015, pp. 1–5.

G. T. Shrivakshan and C. Chandrasekar, “A comparison of various edge detection techniques used in image processing,” Int. J. Comput. Sci. Issues, vol. 9, no. 5, Sep. 2012.

W. Rong, Z. Li, and W. Zhang, "An improved canny edge detection algorithm," in Proc. IEEE Int. Conf. Mechatronics and Automation, Aug. 2014.

T. Semertzidis, K. Dimitropoulos, A. Koutsia, and N. Grammalidis, "Video sensor network for real-time traffic monitoring and surveillance," IET, vol. 4, no. 2, pp. 103–112, Jun. 2010.
E3S Conferences

Z. Hu, W. H. K. Lam, S. C. Wong, A. H. F. Chow, and W. Ma, "Turning traffic monitoring cameras into intelligent sensors for traffic density estimation," arXiv, Oct. 2021.

G. Liu, H. Shi, A. Kiani, A. Khreishah, J. Y. Lee, N. Ansari, C. Liu, and M. Yousef, "Smart traffic monitoring system using computer vision and edge computing," arXiv, Sep. 2021.

K. G. Zoysa and S. R. Munasinghe, "Vision-based incoming traffic estimator using deep neural network on general purpose embedded hardware," arXiv, Oct. 2023.

Wikipedia contributors, "Smart traffic light," Wikipedia, [Online]. Available: Wikipedia. (Accessed Aug. 2025).

Wikipedia contributors, "Scalable urban traffic control," Wikipedia, [Online]. Available: Wikipedia. (Accessed Aug. 2025).